



Descriptif produit

Protect your home with ease thanks to an all-in-one kit that includes sensors, a gateway and wireless control for reliable, connected security.

Accurate motion detection - Motion Sensor ZP1
It detects human presence even in the dark thanks to its infrared technology.
It offers 360° rotation, simple installation with magnetic mounting and up to 2 years of battery life.

Wireless alert button - Wireless Switch ZE1
It triggers an emergency alarm with a single click, sending an instant alert to the app.
Versatile, it can also be used as a remote control to activate various smart scenarios.

Access monitoring - 2x Door & Window Sensors ZD1
They detect any opening of doors, windows or drawers thanks to their magnetic system.
Compact, discreet and easy to install, they have a battery life of 2 years and a tamper-proof design.

Central smart gateway - Smart Gateway ZG2
This is the heart of the system: it manages up to 32 sensors, sends alerts to the app via the cloud and includes a local siren.
Its simplified configuration allows you to activate/deactivate the system with a single gesture.

Compatible WiFi

Color : White

Ref : IMOUKITALARMEWH

EAN : 6976391036154

Pack contents : Smart Alarm Kit 5 elements
+ User Guide/Security/Warranty

Technical characteristics

ZP1 :
Wireless protocol: Zigbee
Transmit power: ≤15dBm
Working voltage: DC 3V
Low pressure alarm: 2.7V
Standby current: ≤15uA
Detection range: 8m
Installation method: Wall-mounted
Battery life: 2 year(20 times/day)
Transmit frequency: 2.4GHz
Communication distance: 200m(open space)
Battery model: CR123V
Operatign temperature: -14°Fto+131°F
Working current: ≤25mA
Sensing angle: 90°
Installation height: 2.2m
Appearance size: Φ48.4x53.4 mm

ZE1 :
Wireless protocol: Zigbee
Transmit power: ≤15dBm
Working voltage: DC 3V
Installation: Destop/Wall-mounted
Battery life: 2 year(20 times/day)
Transmit frequency: 2.4GHz
Communication distance: 200m
Receiving sensitivity : -96dBm
Operatign temperature: -14°Fto+131°F
Appearance size: Φ50x16mm

ZD1 :
Wireless protocol: Zigbee
Transmit power: ≤10dBm
Working voltage: DC 3V
Low pressure alarm: 2.6V
Standby current: ≤10uA
Installation method: Wall-mounted
Battery life: 2 year(20 times/day)
Transmit frequency: 2.4GHz
Communication distance: 200m(open space)
Operatign temperature: -14°Fto+131°F
Working current: ≤30mA
Appearance size:
Sensor-52.6x39.8x13.8 mm
Magnet-25.5x12.5x13.0mm

ZG2 :
Wireless Protocol:Wi-Fi IEEE 802.11 b/g/n 2.4GHz,Zigbee3.0
Operating Voltage:DC 5V
Operating Temperature:-10~55°C
Operating Humidity:0~95%RH, no condensation
Installation Method: desktop & wall mounted
Appearance Size: 68.0x68.0x24.0mm

Compatible mobiles

Compatibilité

Compatible avec : IPHONE 3G .